PRODUCT CODE: **DT-1254-G90**
PUBLICATION DATE: **JULY 2025**

# SUBMITTAL SHEET

12” 54 Mils Deflection Track with 2” Leg (G90)

## PRODUCT INFORMATION

| | |
|---|---|
| Description | **12” 54 Mils Deflection Track with 2” Leg (G90)** |
| Code | **DT-1254-G90** |
| Category | **Structural Deflection Track** |

## GEOMETRIC PROPERTIES

| | |
|---|---|
| Web Depth (in) | **12”** |
| Leg Height (in) | **2”** |
| Weight (lb/ft) | **3.08** |
| Gauge | **16 GA** |
| Design Thickness | **0.0566** |
| Thickness - Mils | **54** |
| Yield Strength Fy (KSI) | **50** |
| Coating | **G90** |

## GROSS SECTION PROPERTIES

| | |
|---|---|
| Cross Section Area **A** | **0.905 in.2** |
| Moment of inertia **Ixx** | **16.464 in.4** |
| Section modulus **Sxx** | **2.699 in.3** |
| Radius of gyration **Rxx** | **4.265 in.** |
| Moment of inertia **Iyy** | **0.236 in.4** |
| Radius of gyration **Ryy** | **0.51 in.** |

## EFFECTIVE SECTION PROPERTIES

| | |
|---|---|
| Moment of inertia for deflection **Ixx** | **12.962 in.4** |
| Section modulus **Sxx** | **1.35 in.3** |
| Allowable bending moment **Ma-L** | **40.41 in.-k** |
| Allowable shear force in web **Va** | **1354 lbs** |

## TORSION PROPERTIES

| | |
|---|---|
| St Venant torsion constant **J1000** | **0.966 in.4** |
| Warping constant **Cw** | **6.714 in.6** |
| Distance from shear center to neutral axis **Xo** | **-0.73 in.** |
| Distance from shear center to mid-plane of web **m** | **0.487 in.** |
| Polar radius of gyration **Ro** | **4.357 in.** |
| Beta **β** | **0.972 β** |

DT-1254-G90



DT-1254-G90 PROFILE

## SUSTAINABILITY & LEED

LEED credit MR 2.1 (1 point)
LEED credit MR 2.2 (1 point)
LEED credit MR 4.1 (1 point)
LEED credit MR 4.2 (1 point)
LEED credit MR 5.1 (1 point)
LEED credit MR 5.2 (1 point)
ISO14001:2015 certified company
Total recycled content 32.7%
(Content: post consumer 25.5%, pre consumer 6.8%)

Suitable for UL Assemblies U419, U465 & U411

## ASTM INFORMATION

All products manufactured by Studco Building Systems are certified to meet or exceed all applicable American Society for Testing & Materials standards as listed below. Studco Building Systems is also accredited to ISO9001- an internationally recognized standard - and an established member of the Steel Stud Manufacturers Association (SSMA).

**Material Specifications (ASTM)**

• All STUDCO Drywall Nonstructural framing members conform to A1003 - A1003 is the Standard specification for steel sheet, Carbon, Metallic- and Nonmetallic- Coated for Cold Formed Framing Members.

**Coating Specifications (ASTM)**

• All STUDCO Drywall Nonstructural framing members conform to C645 - C645 is the Standard specification for Nonstructural Steel Framing Members.

**Product Specifications (ASTM)**

• All STUDCO Drywall Nonstructural framing members conform to C645 - C645 is the Standard specification for Nonstructural Steel Framing Members.

All Drywall Nonstructural products have a G40 minimum weight conforming to ASTM Specification A1003 or have a protective coating with the industry standard requirements of ASTM C645.

All Drywall studs conform to U419, U465 & U411 Standards for Fire Rated Assemblies.

DT-1254-G90_US_0725