PRODUCT CODE: **DT-21243-G90**
PUBLICATION DATE: **JULY 2025**

SUBMITTAL SHEET

2-1/2” 43 Mils Deflection Track with 2” Leg (G90)

PRODUCT INFORMATION

Description	**2-1/2” 43 Mils Deflection Track with 2” Leg (G90)**
Code	**DT-21243-G90**
Category	**Structural Deflection Track**

GEOMETRIC PROPERTIES

Web Depth (in)	**2-1/2”**
Leg Height (in)	**2”**
Weight (lb/ft)	**1**
Gauge	**18 GA**
Design Thickness	**0.0451**
Thickness - Mils	**43**
Yield Strength Fy (KSI)	**50**
Coating	**G90**

GROSS SECTION PROPERTIES

Cross Section Area **A**	**0.293 in.2**
Moment of inertia **Ixx**	**0.366 in.4**
Section modulus **Sxx**	**0.275 in.3**
Radius of gyration **Rxx**	**1.118 in.**
Moment of inertia **Iyy**	**0.126 in.4**
Radius of gyration **Ryy**	**0.657 in.**

EFFECTIVE SECTION PROPERTIES

Moment of inertia for deflection **Ixx**	**0.27 in.4**
Section modulus **Sxx**	**0.15 in.3**
Allowable bending moment **Ma-L**	**4.48 in.-k**
Allowable shear force in web **Va**	**2054 lbs**

TORSION PROPERTIES

St Venant torsion constant **J1000**	**0.198 in.4**
Warping constant **Cw**	**0.153 in.6**
Distance from shear center to neutral axis **Xo**	**-1.413 in.**
Distance from shear center to mid-plane of web **m**	**0.81 in.**
Polar radius of gyration **Ro**	**1.918 in.**
Beta **β**	**0.457 β**



DT-21243-G90



DT-21243-G90 PROFILE

SUSTAINABILITY & LEED

LEED credit MR 2.1 (1 point)
LEED credit MR 2.2 (1 point)
LEED credit MR 4.1 (1 point)
LEED credit MR 4.2 (1 point)
LEED credit MR 5.1 (1 point)
LEED credit MR 5.2 (1 point)
ISO14001:2015 certified company
Total recycled content 32.7%
(Content: post consumer 25.5%, pre consumer 6.8%)

Suitable for UL Assemblies U419, U465 & U411

ASTM INFORMATION

All products manufactured by Studco Building Systems are certified to meet or exceed all applicable American Society for Testing & Materials standards as listed below. Studco Building Systems is also accredited to ISO9001- an internationally recognized standard - and an established member of the Steel Stud Manufacturers Association (SSMA).

Material Specifications (ASTM)

• All STUDCO Drywall Nonstructural framing members conform to A1003 - A1003 is the Standard specification for steel sheet, Carbon, Metallic- and Nonmetallic- Coated for Cold Formed Framing Members.

Coating Specifications (ASTM)

• All STUDCO Drywall Nonstructural framing members conform to C645 - C645 is the Standard specification for Nonstructural Steel Framing Members.

Product Specifications (ASTM)

• All STUDCO Drywall Nonstructural framing members conform to C645 - C645 is the Standard specification for Nonstructural Steel Framing Members.

All Drywall Nonstructural products have a G40 minimum weight conforming to ASTM Specification A1003 or have a protective coating with the industry standard requirements of ASTM C645.

All Drywall studs conform to U419, U465 & U411 Standards for Fire Rated Assemblies.

DT-21243-G90_US_0725