PRODUCT CODE: **ST-454**
PUBLICATION DATE: **JULY 2025**

SUBMITTAL SHEET

4” 54 Mils Structural Track with 1-1/4” Leg (G60)

PRODUCT INFORMATION

Description	**4” 54 Mils Structural Track with 1-1/4” Leg (G60)**
Code	**ST-454**
Category	**Structural Track**

GEOMETRIC PROPERTIES

Web Depth (in)	**4”**
Leg Height (in)	**1-1/4”**
Weight (lb/ft)	**1.25**
Gauge	**16 GA**
Design Thickness	**0.0566**
Thickness - Mils	**54**
Yield Strength Fy (KSI)	**50**
Coating	**G60**

GROSS SECTION PROPERTIES

Cross Section Area **A**	**0.367 in.2**
Moment of inertia **Ixx**	**0.904 in.4**
Section modulus **Sxx**	**0.431 in.3**
Radius of gyration **Rxx**	**1.569 in.**
Moment of inertia **Iyy**	**0.049 in.4**
Radius of gyration **Ryy**	**0.366 in.**

EFFECTIVE SECTION PROPERTIES

Moment of inertia for deflection **Ixx**	**0.849 in.4**
Section modulus **Sxx**	**0.359 in.3**
Allowable bending moment **Ma-L**	**10.74 in.-k**
Allowable shear force in web **Va**	**3372 lbs**

TORSION PROPERTIES

St Venant torsion constant **J1000**	**0.392 in.4**
Warping constant **Cw**	**0.154 in.6**
Distance from shear center to neutral axis **Xo**	**-0.621 in.**
Distance from shear center to mid-plane of web **m**	**0.39 in.**
Polar radius of gyration **Ro**	**1.727 in.**
Beta **β**	**0.871 β**

ST-454



ST-454 PROFILE

SUSTAINABILITY & LEED

LEED credit MR 2.1 (1 point)
LEED credit MR 2.2 (1 point)
LEED credit MR 4.1 (1 point)
LEED credit MR 4.2 (1 point)
LEED credit MR 5.1 (1 point)
LEED credit MR 5.2 (1 point)
ISO14001:2015 certified company
Total recycled content 32.7%
(Content: post consumer 25.5%, pre consumer 6.8%)

Suitable for UL Assemblies U419, U465 & U411

ASTM INFORMATION

All products manufactured by Studco Building Systems are certified to meet or exceed all applicable American Society for Testing & Materials standards as listed below. Studco Building Systems is also accredited to ISO9001- an internationally recognized standard - and an established member of the Steel Stud Manufacturers Association (SSMA).

Material Specifications (ASTM)

• All STUDCO Structural framing members conform to A1003 - A1003 is the Standard specification for steel sheet, Carbon, Metallic- and Nonmetallic - Coated for Cold Formed Framing Members Coating Specification (ASTM) .

• All STUDCO Structural framing members conform to C955 - C955 Standard specification for load-bearing (transverse and axial) steel studs, runners (tracks), and bracing or bridging for screw application of gypsum panel products and metal plaster bases.

Product Specifications (ASTM)

• All STUDCO Structural framing members conform to C955 - C955 Standard specification for load-bearing (transverse and axial) steel studs, runners (tracks), and bracing or bridging for screw application of gypsum panel products and metal plaster bases.

All Structural products have a G60 minimum weight conforming to ASTM Specification A1003 or have a protective coating with the industry standard requirements of ASTM C645. A G90 Coating is available upon request.

All Structural Studs Conform to U420 Standards for Fire Rated Assemblies.

ST-454_US_0725