PRODUCT CODE: **ST-51297-G90**
PUBLICATION DATE: **JULY 2025**

# SUBMITTAL SHEET

5-1/2” 97 Mils Structural Track with 1-1/4” Leg (G90)

## PRODUCT INFORMATION

| | |
|---|---|
| Description | **5-1/2” 97 Mils Structural Track with 1-1/4” Leg (G90)** |
| Code | **ST-51297-G90** |
| Category | **Structural Track** |

## GEOMETRIC PROPERTIES

| | |
|---|---|
| Web Depth (in) | **5-1/2”** |
| Leg Height (in) | **1-1/4”** |
| Weight (lb/ft) | **2.76** |
| Gauge | **12 GA** |
| Design Thickness | **0.1017** |
| Thickness - Mils | **97** |
| Yield Strength Fy (KSI) | **50** |
| Coating | **G90** |

## GROSS SECTION PROPERTIES

| | |
|---|---|
| Cross Section Area **A** | **0.811 in.2** |
| Moment of inertia **Ixx** | **3.483 in.4** |
| Section modulus **Sxx** | **1.19 in.3** |
| Radius of gyration **Rxx** | **2.072 in.** |
| Moment of inertia **Iyy** | **0.09 in.4** |
| Radius of gyration **Ryy** | **0.333 in.** |

## EFFECTIVE SECTION PROPERTIES

| | |
|---|---|
| Moment of inertia for deflection **Ixx** | **3.483 in.4** |
| Section modulus **Sxx** | **1.19 in.3** |
| Allowable bending moment **Ma-L** | **35.62 in.-k** |
| Allowable shear force in web **Va** | **10197 lbs** |

## TORSION PROPERTIES

| | |
|---|---|
| St Venant torsion constant **J1000** | **2.797 in.4** |
| Warping constant **Cw** | **0.564 in.6** |
| Distance from shear center to neutral axis **Xo** | **-0.514 in.** |
| Distance from shear center to mid-plane of web **m** | **0.333 in.** |
| Polar radius of gyration **Ro** | **2.161 in.** |
| Beta **β** | **0.943 β** |

**ST-51297-G90**



**ST-51297-G90 PROFILE**

## SUSTAINABILITY & LEED

LEED credit MR 2.1 (1 point)
LEED credit MR 2.2 (1 point)
LEED credit MR 4.1 (1 point)
LEED credit MR 4.2 (1 point)
LEED credit MR 5.1 (1 point)
LEED credit MR 5.2 (1 point)
ISO14001:2015 certified company
Total recycled content 32.7%
(Content: post consumer 25.5%, pre consumer 6.8%)

Suitable for UL Assemblies U419, U465 & U411

## ASTM INFORMATION

All products manufactured by Studco Building Systems are certified to meet or exceed all applicable American Society for Testing & Materials standards as listed below. Studco Building Systems is also accredited to ISO9001- an internationally recognized standard - and an established member of the Steel Stud Manufacturers Association (SSMA).

**Material Specifications (ASTM)**

• All STUDCO Structural framing members conform to A1003 - A1003 is the Standard specification for steel sheet, Carbon, Metallic- and Nonmetallic - Coated for Cold Formed Framing Members Coating Specification (ASTM) .

• All STUDCO Structural framing members conform to C955 - C955 Standard specification for load-bearing (transverse and axial) steel studs, runners (tracks), and bracing or bridging for screw application of gypsum panel products and metal plaster bases.

**Product Specifications (ASTM)**

• All STUDCO Structural framing members conform to C955 - C955 Standard specification for load-bearing (transverse and axial) steel studs, runners (tracks), and bracing or bridging for screw application of gypsum panel products and metal plaster bases.

All Structural products have a G60 minimum weight conforming to ASTM Specification A1003 or have a protective coating with the industry standard requirements of ASTM C645. A G90 Coating is available upon request.

All Structural Studs Conform to U420 Standards for Fire Rated Assemblies.



**For Sales Inquiries, please contact Studco Building Systems on 800.675.8023**
Studco Building Systems US LLC 1700 Boulter Industrial Parkway Webster NY 14580 USA www.studcosystems.com